

Rustfri

Svejste rustfri firkantrør

Svejste rustfri firkantrør, i fabriklængder på 6000 mm

-0/+100 mm. I børstet eller ubehandlet udførelse, hvor andet ikke er angivet.

Dimension			Vægt Kg/m	Udførelse	EN 1.4307 EN 1.4301	EN 1.4404	EN 1.4571
U.D.	U.D.	Gods					
10	10	1,0	0,300		X		
15	15	1,0	0,463		X		
15	15	1,5	0,676	K240/K320	X		
15	15	1,5	0,676		X		
15	15	1,5	0,676	K240/K320	X		
20	10	1,2	0,538		X		
20	10	1,2	0,538	K240/K320	X		
20	10	1,5	0,676		X		
20	10	1,5	0,676	K240/K320	X		
20	15	1,5	0,798		X		
20	15	1,5	0,798	K240/K320	X		
20	20	1,0	0,626	K240/K320	X		
20	20	1,2	0,745		X		
20	20	1,2	0,745	K240/K320	X		
20	20	1,5	0,920		X		
20	20	1,5	0,920	K240/K320	X		X
20	20	2,0	1,202		X		
20	20	2,0	1,202	K240/K320	X		
20	20	2,0	1,202				X
25	10	1,5	0,798		X		
25	10	1,5	0,798	K240/K320	X		
25	15	1,5	0,920		X		
25	15	1,5	0,920	K240/K320	X		
25	25	1,2	0,941	K240/K320			
25	25	1,2	0,941		X		
25	25	1,2	0,941	K240/K320	X		
25	25	1,5	1,164		X		
25	25	1,5	1,164	K240/K320	X		
25	25	1,5	1,164				X
25	25	2,0	1,527		X		
25	25	2,0	1,527	K240/K320	X		
25	25	2,0	1,527				X
25	25	3,0	2,216		X		
30	10	1,5	0,920		X		
30	10	1,5	0,920	K240/K320	X		
30	15	1,2	0,825		X		
30	15	1,2	0,825	K240/K320	X		
30	15	1,5	1,042		X		
30	15	1,5	1,042	K240/K320	X		
30	15	1,5	1,042				X
30	15	2,0	1,365		X		
30	15	2,0	1,365	K240/K320	X		
30	20	1,2	0,921	K240/K320	X		

Dimension			Vægt Kg/m	Udførelse	EN 1.4307 EN 1.4301	EN 1.4404	EN 1.4571
U.D.	U.D.	Gods					
30	20	1,2	0,921	K240/K320	X		
30	20	1,5	1,164		X		
30	20	1,5	1,164	K240/K320	X		
30	20	2,0	1,527		X		
30	20	2,0	1,527	K240/K320	X		
30	20	2,0	1,527				X
30	30	1,2	1,136	K240/K320	X		
30	30	1,2	1,136		X		
30	30	1,5	1,409		X		
30	30	1,5	1,409	K240/K320	X		
30	30	1,5	1,409				X
30	30	2,0	1,853		X		
30	30	2,0	1,853	K240/K320	X		
30	30	2,0	1,853				X
30	30	3,0	2,704		X		
30	30	3,0	2,704	K240/K320	X		
30	30	3,0	2,704				X
35	20	1,5	1,259		X		
35	35	1,2	1,303		X		
35	35	1,2	1,303	K240/K320	X		
35	35	1,5	1,653		X		
35	35	1,5	1,653	K240/K320	X		
35	35	2,0	2,178	K240/K320	X		
35	35	2,0	2,178		X		
35	35	2,0	2,178				X
35	35	3,0	3,193		X		
40	15	1,5	1,286		X		
40	20	1,2	1,136		X		
40	20	1,2	1,136	K240/K320	X		
40	20	1,5	1,409		X		
40	20	1,5	1,409	K240/K320	X		
40	20	2,0	1,853		X		
40	20	2,0	1,853	K240/K320	X		
40	20	2,0	1,853				X
40	20	3,0	2,650		X		
40	27	1,5	1,536		X		
40	30	1,2	1,303	K240/K320	X		
40	30	1,5	1,653		X		
40	30	1,5	1,653	K240/K320	X		
40	30	2,0	2,178		X		
40	30	2,0	2,178	K240/K320	X		
40	30	2,0	2,178				X
40	30	3,0	3,193		X		
40	40	1,0	1,243	K240/K320	X		
40	40	1,0	1,243		X		
40	40	1,2	1,526		X		
40	40	1,2	1,526	K240/K320	X		
40	40	1,3	1,544		X		
40	40	1,3	1,544	K240/K320	X		
40	40	1,5	1,897	K240/K320	X		
40	40	1,5	1,897		X		
40	40	2,0	2,504		X		
40	40	2,0	2,504	K240/K320	X		
40	40	2,0	2,504				X

Dimension			Vægt Kg/m	Udførelse	EN 1.4307 EN 1.4301	EN 1.4404	EN 1.4571
U.D.	U.D.	Gods					
40	40	3,0	3,681		X		
40	40	3,0	3,681			X	
40	40	3,0	3,681	K240/K320	X		
40	40	3,0	3,681				X
40	40	4,0	4,808		X		
40	40	4,0	4,808				X
45	45	2,0	2,830		X		
45	45	2,0	2,830	K240/K320	X		
50	20	1,5	1,653		X		
50	20	1,5	1,653	K240/K320	X		
50	20	2,0	2,178		X		
50	20	2,0	2,178	K240/K320	X		
50	20	2,0	2,178				X
50	25	1,5	1,775		X		
50	25	1,5	1,775	K240/K320	X		
50	25	1,5	1,775				X
50	25	2,0	2,341	K240/K320	X		
50	25	2,0	2,341		X		
50	25	2,0	2,341				X
50	30	1,5	1,897		X		
50	30	1,5	1,897	K240/K320	X		
50	30	1,5	1,897				X
50	30	2,0	2,504		X		
50	30	2,0	2,504	K240/K320	X		
50	30	2,0	2,504				X
50	30	3,0	3,681		X		
50	30	3,0	3,681	K240/K320	X		
50	30	3,0	3,681				X
50	40	2,0	2,803		X		
50	40	2,0	2,803	K240/K320	X		
50	40	2,0	2,803				X
50	40	3,0	4,169		X		
50	50	1,5	2,385		X		
50	50	1,5	2,385	K240/K320	X		
50	50	1,5	2,385				X
50	50	2,0	3,155		X		
50	50	2,0	3,155	K240/K320	X		
50	50	2,0	3,155				X
50	50	3,0	4,657		X		
50	50	3,0	4,657	K240/K320	X		
50	50	3,0	4,657				X
50	50	4,0	6,110		X		
50	50	4,0	6,110	K240/K320	X		
50	50	4,0	6,110				X
50	50	5,0	7,512		X		
60	20	1,5	1,897		X		
60	20	1,5	1,897	K240/K320	X		
60	20	2,0	2,504		X		
60	20	2,0	2,504	K240/K320	X		
60	20	2,0	2,504				X
60	30	1,5	2,141		X		
60	30	1,5	2,141	K240/K320	X		
60	30	1,5	2,141				X
60	30	2,0	2,830	K240/K320	X		
60	30	2,0	2,830		X		

Dimension			Vægt Kg/m	Udførelse	EN 1.4307 EN 1.4301	EN 1.4404	EN 1.4571
U.D.	U.D.	Gods					
60	30	2,0	2,830				X
60	30	3,0	4,169		X		
60	30	3,0	4,169	K240/K320	X		
60	30	3,0	4,169				X
60	40	1,5	2,385		X		
60	40	2,0	3,155		X		
60	40	2,0	3,155	K240/K320	X		
60	40	2,0	3,155				X
60	40	3,0	4,657		X		
60	40	3,0	4,657	K240/K320	X		
60	40	3,0	4,657				X
60	40	4,0	6,110		X		
60	40	4,0	6,110				X
60	60	1,5	2,873		X		
60	60	1,5	2,873	K240/K320	X		
60	60	2,0	3,806	K240/K320	X		
60	60	2,0	3,806		X		
60	60	2,0	3,806				X
60	60	3,0	5,634		X		
60	60	3,0	5,634	K240/K320	X		
60	60	3,0	5,634				X
60	60	4,0	7,412		X		
60	60	4,0	7,412	K240/K320	X		
60	60	4,0	7,412				X
60	60	5,0	9,140		X		
60	60	5,0	9,140				X
70	40	2,0	3,405		X		
70	40	3,0	5,146		X		
70	70	2,0	4,457		X		
70	70	3,0	6,611		X		
70	70	3,0	6,611				X
70	70	4,0	8,714		X		
70	70	4,0	8,714				X
70	70	5,0	10,767		X		
80	30	3,0	5,146		X		
80	40	1,5	2,873		X		
80	40	1,5	2,873	K240/K320	X		
80	40	2,0	3,806	K240/K320	X		
80	40	2,0	3,806		X		
80	40	2,0	3,806				X
80	40	3,0	5,634		X		
80	40	3,0	5,634	K240/K320	X		
80	40	3,0	5,634				X
80	40	4,0	7,412		X		
80	40	4,0	7,412				X
80	40	5,0	9,140		X		
80	50	2,0	4,132		X		
80	50	3,0	6,122		X		
80	50	5,0	9,850		X		
80	60	2,0	4,557		X		
80	60	2,0	4,557				X
80	60	3,0	6,611		X		
80	60	3,0	6,611	K240/K320	X		
80	60	3,0	6,611				X
80	60	4,0	8,714		X		

Dimension			Vægt Kg/m	Udførelse	EN 1.4307 EN 1.4301	EN 1.4404	EN 1.4571
U.D.	U.D.	Gods					
80	60	4,0	8,714				X
80	60	5,0	10,540		X		
80	80	2,0	5,108		X		
80	80	2,0	5,108	K240/K320	X		
80	80	2,0	5,108				X
80	80	3,0	7,587		X		
80	80	3,0	7,587	K240/K320	X		
80	80	3,0	7,587				X
80	80	4,0	10,016		X		
80	80	4,0	10,016	K240/K320	X		
80	80	4,0	10,016				X
80	80	5,0	12,395		X		
80	80	5,0	12,395				X
80	80	6,0	14,724		X		
90	90	3,0	8,388		X		
90	90	4,0	11,050		X		
100	40	2,0	4,457		X		
100	40	2,0	4,457	K240/K320	X		
100	40	3,0	6,611		X		
100	40	3,0	6,611				X
100	40	4,0	9,365		X		
100	40	4,0	9,365				X
100	50	2,0	4,783		X		
100	50	2,0	4,783				X
100	50	3,0	7,099		X		
100	50	3,0	7,099	K240/K320	X		
100	50	4,0	9,365		X		
100	50	4,0	9,365				X
100	50	5,0	11,581		X		
100	50	5,0	11,581				X
100	50	6,0	14,648		X		
100	60	2,0	5,108		X		
100	60	2,0	5,108				X
100	60	3,0	7,587		X		
100	60	3,0	7,587	K240/K320	X		
100	60	4,0	10,016		X		
100	60	4,0	10,016	K240/K320	X		
100	60	4,0	10,016				X
100	60	5,0	12,395		X		
100	60	5,0	12,395				X
100	60	6,0	14,600		X		
100	80	3,0	8,564		X		
100	80	3,0	8,564				X
100	80	4,0	11,318		X		
100	80	5,0	13,750		X		
100	100	2,0	6,410		X		
100	100	2,0	6,410	K240/K320	X		
100	100	2,0	6,410				X
100	100	3,0	9,540		X		
100	100	3,0	9,540	K240/K320	X		
100	100	3,0	9,540				X
100	100	4,0	12,620		X		
100	100	4,0	12,620				X

Dimension			Vægt Kg/m	Udførelse	EN 1.4307 EN 1.4301	EN 1.4404	EN 1.4571
U.D.	U.D.	Gods					
100	100	5,0	15,650				X
100	100	6,0	18,630		X		
100	100	6,0	18,630				X
100	100	8,0	21,500		X		
120	40	2,0	5,108		X		
120	40	3,0	7,587	K240/K320	X		
120	40	3,0	7,587		X		
120	40	4,0	9,807		X		
120	60	2,0	5,759		X		
120	60	3,0	8,564		X		
120	60	3,0	8,564	K240/K320	X		X
120	60	3,0	8,564				X
120	60	4,0	11,318		X		
120	60	4,0	11,318				X
120	60	5,0	14,022		X		
120	60	5,0	14,022				X
120	60	6,0	16,677		X		
120	80	2,0	6,410		X		
120	80	2,0	6,410	K240/K320	X		
120	80	3,0	9,540		X		
120	80	3,0	9,540	K240/K320	X		X
120	80	3,0	9,540				X
120	80	4,0	12,620		X		
120	80	4,0	12,620				X
120	80	5,0	15,650		X		
120	80	6,0	18,630		X		
120	120	2,0	7,555		X		
120	120	3,0	11,493		X		
120	120	3,0	11,493	K240/K320	X		
120	120	3,0	11,493				X
120	120	4,0	15,224		X		
120	120	4,0	15,224				X
120	120	5,0	18,905		X		
120	120	5,0	18,905				X
120	120	6,0	22,536		X		
140	80	3,0	10,517		X		
140	80	4,0	13,922		X		
140	80	5,0	17,287		X		
140	140	5,0	21,120		X		
150	50	3,0	9,540		X		
150	50	3,0	9,540				X
150	50	4,0	12,620		X		
150	50	5,0	15,650		X		
150	80	5,0	17,709		X		
150	100	3,0	11,982		X		
150	100	3,0	11,982				X
150	100	4,0	15,875		X		
150	100	5,0	19,719		X		
150	100	6,0	23,513		X		
150	100	6,0	23,513				X
150	100	10,0	33,650		X		
150	150	3,0	14,423		X		
150	150	4,0	19,131		X		
150	150	4,0	19,131				X
150	150	5,0	23,788		X		

Dimension			Vægt Kg/m	Udførelse	EN 1.4307 EN 1.4301	EN 1.4404	EN 1.4571
U.D.	U.D.	Gods					
150	150	5,0	23,788				X
150	150	6,0	28,359		X		
150	150	8,0	37,460		X		
160	80	3,0	11,493		X		
160	80	4,0	15,224		X		
160	80	5,0	18,905		X		
160	80	5,0	18,905				X
200	100	3,0	14,423		X		
200	100	4,0	19,131		X		
200	100	5,0	23,788		X		
200	100	6,0	28,395		X		
200	150	4,0	21,400		X		
200	200	3,0	19,306		X		
200	200	4,0	25,641		X		
200	200	5,0	31,962		X		
200	200	6,0	38,161		X		
250	100	3,0	17,089		X		
250	100	4,0	22,386		X		
250	100	5,0	27,857		X		
250	100	8,0	40,700		X		
250	150	4,0	25,641		X		
250	150	5,0	30,962		X		
250	150	10,0	62,600		X		